

OBSERVATION ELEVATORS

for a greener tomorrow Change



VIEW

2nd Edition

F

Adding Drama and Funtothe Elevator Ride





Observation elevators make traveling between floors within a building a dramatic and exciting experience. Mitsubishi Electric's latest line-up of observation elevators builds on its most popular designs, and expands the view by adding even more window space. In addition, customers can mix and match components to create the ideal elevator for a particular building or purpose, whether it is hotel, mall or office, indoor or outdoor. A range of popular standard elevator types are also available, offering cost performance and proven quality. Any of the new models, component-type or standard, will add an exciting new dimension to elevator travel, with light, space and visible motion.



Contents

1-2 Introduction
3-10 Component Type
11-12 Standard Type
13-20 Actual Installation Examples
21-22 Installation List



COMPONENT TYPE A Futuristic Capsule

INDOOR OPEN TYPE INDOOR/OUTDOOR ENCLOSED TYPE* **KYO1A** Round

CAR SECTION

EXTERIOR (Car design example)

- Windows: Transparent curved glass (option: lightly tinted glass)
- Upper and lower shells: Fiber-reinforced plastic with painted finish (Y051)
- Mullions: Painted steel sheet (Y051)
- Decorative lighting: Globular, milky-white acrylic plate illuminated from inside, at shell top and bottom

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Fluorescent lighting through circular, milky-white acrylic plate, and downlights
- Wall and doors: Stainless-steel, hairline-finish
 Handrail: Single line of hairline-finished
- stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.

* For Enclosed Type, it's needed to provide the carry-in entrance for outer panel at the shaft wall of observation side because it's unable to carry in the outer panel from hall side.





COMPONENT TYPE A Bold Spaceship



CAR SECTION



- Windows: Transparent curved glass (option: lightly tinted glass)
- Upper and lower shells: Fiber-reinforced plastic with painted finish (Y002)
- Mullions: Painted steel sheet (Y002)
- Decorative lighting: Three rings of milkywhite acrylic plate illuminated from inside around upper and lower shells
- Shell top and bottom lighting: Circular, milky-white acrylic plate illuminated from inside

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Fluorescent lighting through circular, milky-white acrylic plate, and downlights
- Wall and doors: Stainless-steel, hairline-finish
- Handrail: Single line of hairline-finished stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.

* For Enclosed Type, it's needed to provide the carry-in entrance for outer panel at the shaft wall of observation side because it's unable to carry in the outer panel from hall side.



COMPONENT TYPE An Airy Glass Cabin

INDOOR OPEN TYPE INDOOR/OUTDOOR ENCLOSED TYPE KYO3A Octagonal

CAR SECTION



EXTERIOR (Car design example)

- Windows: Transparent flat glass (option: lightly tinted glass)
- Upper and lower shells: Painted steel sheet (Y054)
- Mullions: Painted steel sheet (Y054)
- Decorative lighting: Downlights at shell bottom

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Downlights

5

- Wall and doors: Stainless-steel, hairline-finish
- Handrail: Single line of hairline-finished stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.





COMPONENT TYPE A Modern Angular Design



A Cylindrical Pod

HY05A Horseshoe

CAR SECTION



EXTERIOR (Car design example)

- Windows: Transparent curved glass (option: lightly tinted glass)
- Upper and lower shells: Painted steel sheet (Y116)
- Mullions: Painted steel sheet (Y116)
- Decorative lighting: Downlights

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Fluorescent lighting through circular, milky-white acrylic plate, and downlights.
- Wall and doors: Stainless-steel, hairline-finish
- Handrail: Single line of hairline-finished stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.

7





A Stark Square Box



COMPONENT TYPE A Bright, Airy Box



CAR SECTION



EXTERIOR (Car design example)

- Windows: Transparent flat glass (option: lightly tinted glass)
- Upper and lower shells: Painted steel sheet (Y014)
- Mullions: None
- Decorative lighting: Downlights

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Downlights
- Wall and doors: Stainless-steel, hairline-finish
- Handrail: Single line of hairline-finished stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.





COMPONENT TYPE A Sleek, Narrow Window Design

OUTDOOR ENCLOSED TYPE SY08 Square

CAR SECTION

EXTERIOR (Car design example)

- Windows: 500mm width transparent flat glass (option: lightly tinted glass)
- Upper and lower shells: None
- Window frames: Anodized aluminum finish
- Decorative lighting: None

INTERIOR (Car design example)

- Ceiling: Painted steel sheet (Y033)
- Lighting: Fluorescent lighting through milky-white acrylic cover (basic design)
- Wall: Pattern-printed steel sheet (CP23) • Handrail: Single line of hairline-finished
- stainless-steel pipe • Kick-plate: Stainless-steel, hairline-finish
- Flooring: Vinyl tiles (PR803)

OUTSIDE VIEW



Car outline shows cage and window only. Other features have been omitted for clarity.

A Simple, No-Frills Design



11





standard type Square Box



NY21B Square

CAR SECTION

EXTERIOR (Car design example)

- Windows: Transparent flat glass (option: lightly tinted glass)
- Upper and lower shells: Painted steel sheet (Y006)
- Mullions: Painted steel sheet (Y006)
- Decorative lighting: None (available as an option)

INTERIOR (Car design example)

- Ceiling: Painted steel sheet
- Lighting: Fluorescent lighting through milky-white acrylic cover (basic design)
- Front wall and doors: Pattern-printed steel sheet (CP23)
- Handrail: Single line of hairline-finished stainless-steel pipe
- Mullions: Stainless-steel, hairline-finish

Car outline shows cage and window only. Other features have been omitted for clarity.

Abu Dhabi, UAE | Emirates Palace Hotel



Doha, Qatar | City Centre









Dubai, UAE | Emirates Tower



Riyadh, Saudi Arabia | Al Faisaliah Center







London, UK | 100VE





Buenos Aires, Argentina | Hilton Buenos Aires







Bangkok, Thailand | Siam Paragon



Kuala Lumpur, Malaysia | Berjaya Times Square







Beijing, China | CYTS Plaza



Shanghai, China | Jin Jiang Tower





Taiwan | Core Pacific City



Taiwan | Ambassador Hotel Hsinchu









Hong Kong | Hong Kong International Airport





Osaka, Japan | Osaka Maritime Museum







Tokyo, Japan | Sumida Riverside Hall



Aichi, Japan | Midland Square



Observation double-deck elevators







Installation List

Overseas

CUSTOMER	CAR SPEED (m/min)	CAPACITY (kg)	NBR. OF CARS	COUNTRY/ AREA
Asia Hotel	120	1,150	1	China
CYTS Plaza	150	1,350	6	China
Hua Ting Hotel	105	1,600	2	China
Jin Jiang Tower	105	1,600	2	China
Shanghai Jin Mao Building	105	1,600	2	China
Hong Kong International Airport	60	2,700	6	Hong Kong
Ambassador Hotel Hsinchu	105	1,150	3	Taiwan
Core Pacific City	105	1,600	1	Taiwan
Regency Hotel	90	750	4	Taiwan
Hotel Lotte Shinkan	120	1,800	3	Korea
Hotel Lotte World	45 / 210	1,350 / 1,350	2 / 1	Korea
Berjaya Times Square	60	1,150	3	Malaysia
Securities Commission	90	1,155	4	Malaysia
Wilayah Shopping Complex	60	1,000	1	Malaysia
Hotel Meridien	90	1,360	4	Singapore
Marina Mandarin Hotel	150	1,565	4	Singapore
Oriental Hotel	150	1,565	6	Singapore
Pan Pacific Hotel	150 / 210	1,565 / 1,565	4 / 4	Singapore
Central City Bangna	90	1,150	8	Thailand
Jewelry Trade Center	60	1,150	2	Thailand
Siam Paragon	105 / 105	1,600 / 1,800	2 / 2	Thailand
Abu Dhabi Trade Centre	45 / 105	1,600 / 1,600	2 / 2	UAE
Burj Al Arab	300	2,000	2	UAE
Dubai International Airport	60	1,135	4	UAE
Emirates Palace Hotel	105	1,000	4	UAE
Emirates Tower	240	1,400	4	UAE
City Centre	60	1,000	8	Qatar
Doha Sheraton Hotel	150	1,350	5	Qatar
Tat Tower	105	1,000 / 1,350	4	Turkey
Al Faisaliah Center	30 / 60 / 105 / 105	1,150 / 1,600 / 1,150 / 1,6	00 1/3/2/4	Saudi Arabia
AI-Mahmal Commercial Center and Tower	90	1,400	2	Saudi Arabia
First Makkah Residential and Commercial Complex	60 / 180	1,350 / 1,350	6 / 4	Saudi Arabia
Meridien Galleria	60	1,350	1	Egypt
Emerald Shapery Center	105 / 150	1,600 / 1,600	2 / 2	USA
Centro Asturiano	60	1,400	4	Mexico
Hotel Royal Zona Rosa	105	1,050	2	Mexico
Hotel Cosmos 100	90	900	1	Colombia
Hilton Buenos Aires	90	1.350	4	Argentina
ING House	96	1,250	2	The Netherland
88 Wood Street	150	1,250	6	UK
100VE	96	1,600	6	UK

Japan

CUSTOMER	CAR SPEED (m/min)	CAPACITY (kg)	NBR. Of Cars	AREA
Aquamarine Fukushima	90	1,600	1	Fukushima
Century Tower	90 / 150 / 300	600 / 850 / 850	2 / 6 / 6	Tokyo
Meguro Gajoen	60	1,600	1	Tokyo
Sumida Riverside Hall	180	1,600 2	3	Tokyo
Queens Square Yokohama	60	1,000	2	Kanagawa
Yokohama Grand Intercontinental Hotel	150	1,500	2	Kanagawa
Hotel New Otani Makuhari	240	1,350	1	Chiba
Hakuba Cortina Resort Villa	90	1,000	2	Nagano
Sunship Toyama	60	1,350	2	Toyama
Kagaya-Setsugekka	105	750	3	Ishikawa
Aichi Arts Center	150	1,600	3	Aichi
Higashiyama Sky Tower	90	1,200	2	Aichi
JR Central Towers	210	2,600	6	Aichi
Midland Square	360 / 90	2,150 2/1,600	4 / 3	Aichi
Obu City Public Office Building	90	1,150	2	Aichi
Asia Pacific Trade Center	105	1,600	3	Osaka
Big Step	105	1,350	3	Osaka
Hep Five	120	1,650	2	Osaka
Kansai International Airport	45	1,800	10	Osaka
Osaka Maritime Museum	60 / 45	1,800 / 1,300	3 / 3	Osaka
Hotel Kyocera	105	1,300	3	Kagoshima

Points to Consider when Planning Installation

- 1. Prices and delivery schedules vary greatly depending on such factors as design, materials, finish, car shape and installation conditions.
- 2. Adequate space should be allowed for the elevator hoistway (inner dimensions, pit depth, overhead, etc.) so that no restrictions are placed on car shape or exterior trim design.
- 3. If air conditioning equipment is installed on the car, it is requested that drainage facilities be placed in the pit.
- 4. It is requested that for the outdoor enclosed model sufficient ventilation and air conditioning be provided so that the machinery installed in the elevator hoistway and machine room is not exposed to high temperatures as a result of direct sunlight. In addition, please consider the use of thermal insulation glass on the building side as required. (Customer is responsible for construction in each case.)

In cold regions, measures should be taken to protect machinery against low temperatures and condensation. Measures include the use of thermal insulation glass on the building side and warm-air blowers for the elevator hoistway. (Customer is responsible for construction.)

- 5. Mitsubishi Electric has also supplied many outdoor open observation elevators.
- (1) Please note that there are restrictions as to the shape, materials and design of outdoor models because special measures such as waterproofing and rustproofing are required.
- (2) Elevator operations will be interrupted during high winds for reasons of safety. Therefore, it is requested that a wind gauge and a dome for evacuation be installed. (Customer is responsible for construction.)
- (3) It is requested that the installation of this model elevator be avoided in cold regions because such accidents as cable slippage due to machinery icing are possible.
- * It is requested that Mitsubishi Electric specialists, through its affiliated companies, be consulted during the early stages of planning in regard to the aforementioned items and any other matters considered necessary.





Mitsubishi Elevator Inazawa Works has acquired ISO 9001 certification from the International Organization for Standardization based on a review of quality management. The company has also acquired environmental management system standard ISO 14001 certification.



Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.

MITSUBISHI ELECTRIC CORPORATION HEAD OFFICE : TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

Visit our website at: http://www.mitsubishielectric.com/elevator/

A Safety Tips: Be sure to read the instruction manual fully before using this product.